

## CableCom-E



Part-No.: 0310020



Part-No.: 0310021 (plug-in coupling)

The CableCom-E is an acoustic insulated hearing protection headset equipped with a noise cancelling gooseneck microphone. It offers wired communication in full duplex most suitable for noisy environments like at assembly sites, machine rooms and communications on ships.

This headset holds an integrated LF-amplifier (low frequency) and enables communication among each other in a group up to 10 units. The on/off button at the lower end of the ear protection it is to adjust the volume. To connect the headset to the coiled cord, either use a 6.35 mm plug or connector.

Besides, the ergonomically formed, well cushioned hearing protection capsules, as well as the wide head holder offer high wearing comfort for hours.

### Technical data:

#### **Microphone:**

Pattern:	electret
Directional:	noise cancelling (NC)
Impedance:	4400 Ohm
Sensitivity:	-44 dB V / Pa, 1 kHz
Frequency range:	300 Hz – 9 kHz

#### **Speaker:**

Pattern:	dynamic
Impedance:	300 Ohm at 1 mW / 1 kHz
Sound pressure level:	max. 115 dB
Frequency range:	150 Hz – 12 kHz

#### **Additional Data:**

Operating voltage:	9 V
Operating time:	Rechargeable battery approx. 10 h / battery approx. 30 h
Power input:	12 mA
Noise attenuation:	approx. 27 dB
Temperature range:	-30°C to +70°C
Weight:	570 g (incl. coiled cord)

TECHNICAL DATA