

HT2-ATC



Part-No.: 0229109-21



Part-No.: 640-033 (Holder for table) / Tower

The hand microphone HT2-ATC is made of anodized aluminium. It offers a high attenuation of impact sound and holds high-quality acoustic components. Optionally, the HT2-ATC is available with or without send button.

Further to the classical black colour, Imtradex also offers the HT2-ATC in a silver matt-finished aluminium design. As valuable accessory, you can also order a holder to mount this hand microphone to a convenient place at your workstation.

Technical data:

Microphone:

Pattern:	electret
Directional:	omni-directional
Impedance:	2200 Ohm
Sensitivity:	-36 dB V / Pa, 1 kHz
Frequency:	20 Hz – 16 kHz

Amplifier:

Operating voltage:	+/- 12 V
Power Input:	15 mA
Distortion factor:	0,2 %
Amplification:	ca. 26 dB

Cable specification (Design):

Cord:	Steel cord
Cord diameter:	0,07 mm ²
Insulation of cord:	PETP (Polyamide)
Shield:	Cu – round twist density > 90%
Insulation of coating:	PUR (Polyurethane)
Strength steal wires:	> 2000 N/mm ²
Tensile strength lead:	> 120 N

Additional data:

MTBF:	approx. 100.000 h.
Life cycle PTT:	min. 500.000 cycles
Length:	156 mm
Diameter:	25 mm
Temperature range:	-20°C to +70°C
Weight:	202 g

TECHNICAL DATA