

## PTT-13



Part-No.,: 06PTT13



To use in Dispatch places and Control Centres

The PTT-13 is an ergonomically formed send button, designed like the handle of a gun. This shape supports to operate the send button intuitively, regardless the biggest rush. Consequently, the PTT-13 supports fatigue-proof and wrist sparing operation. On the technical side, the PTT-13 is comparable to the PTT-19, as both send buttons are equipped with the same technical components.

Like the PTT-19, the PTT-13 offers a high-resistant send button that ensures long-lasting durability though facing heavy duty demands. The housing, made of impact resistant polystyrene fulfils the requirements of protection classification IP43 and provides sufficient space for electronically adaption to the VCS (Voice Communication System), used. Thanks to a clip, the send button is easy to wear at a belt.

### Technical data:

#### **Housing:**

Material: PC/ABS T45, black  
Dielectric strength 1 mm: 40 kV/mm (IEC 243 T1 / DIN 53481)

#### **Switching element:**

Contact resistance: max. 30 MOhm  
Isolation resistance: >10 MOhm  
Switching performance: 0, 71 W  
Life cycle PTT: 10.000.000 cycles

#### **Additional data:**

Temperature range: -20°C to +70°C  
Dimensions (LxWxH): 108 mm x 40 mm x 20 mm  
Weight: approx. 39 g  
Protection class: IP43<sup>1</sup>

<sup>1</sup> Protection class: DIN EN 61058-1 VDE 0630 Part 1, EN 60529:1991 DIN VDE 0470-1:1992-11

TECHNICAL DATA