

PTT-19



Part-No.: 06PTT19



To use in Dispatch places and Control Centres

The PTT-19 is an ergonomically designed send button, made of impact resistant polystyrene. This fatigue-proof ergonomic design is of big advantage regarding the efforts of operations with a high level of public safety. The send button offers a definite pressure point and a mechanical stop position. This ensures long-lasting durability though facing heavy duty demands.

The housing fulfils the requirements of protection classification IP43 and provides sufficient space for the electronically adaptation to the VCS (Voice Communication System) used. Usually, the send button is equipped with a clip. Upon request, it can also be delivered without. Due to the ergonomically shaped back side, the PTT-19 is also convenient to operate when holding in the hand.

Technical data:

Housing:

Material: PC/ABS T45, black
Dielectric strength 1 mm: 40 kV/mm (IEC 243 T1 / DIN 53481)

Switching element:

Contact resistance: max. 30 MOhm
Isolation resistance: >10 MOhm
Switching performance: 0, 71 W
Life cycle PTT: 10.000.000 cycles

Additional data:

Temperature range: -20°C to +70°C
Dimensions (LxWxH): 101 mm x 39 mm x 22 mm
Weight: approx. 39 g
Protection class: IP43¹

¹ Protection class: DIN EN 61058-1 VDE 0630 Part 1, EN 60529:1991 DIN VDE 0470-1:1992-11

TECHNICAL DATA