

Мы оставляем за собой право вносить изменения в характеристики продукта в результате технического прогресса (данные на июль 2011 г.)

ККМ-РТТ



Код: 06ax070-1



Рабочий в защитной одежде

ККМ-РТТ состоит из ларингофона, наушника и крупной кнопки ответа. Работает с аналоговыми или цифровыми рациями. Благодаря легкости, удобному дизайну и независимости от используемого шлема, ККМ-РТТ считается оптимальным решением при работе в респираторе и защитной одежде.

Большая кнопка ответа РТТ-8 оснащена клипсой для крепления на одежду, поворачивающейся на 360°. Кнопку ответа удобно использовать даже с защитной одеждой. Электрические характеристики РТТ-8 позволяют подключать гарнитуру к любой аналоговой или цифровой рации.

Technical data:

Throat microphone:

Pattern:	electret
Directional:	n.n
Impedance:	2000 Ohm
Sensitivity:	-41 dB V / Pa, 1 kHz
Frequency range:	400 Hz – 4 kHz

Speaker:

Type:	dynamic
Impedance:	320 Ohm at 1 mW / 1 kHz
Sound pressure level:	max. 98 dB
Frequency range:	300 Hz – 8 kHz

Send button (PTT-8):

Housing:	impact resistant plastic housing, black, with cloth clip
Life cycle PTT:	min. 1.500.000 cycles
Protection class:	IP54 ¹

Additional data:

Temperature range:	-20°C to +70°C
Weight:	160 g

¹ Protection class: DIN EN 61058-1 VDE 0630 Part 1, EN 60529:1991 DIN VDE 0470-1:1992-11

Digital Standard approved

