

Мы оставляем за собой право вносить изменения в характеристики продукта в результате технического прогресса (данные на июль 2011 г.)

OnGuard III



Код: 0131000-7 (бежевый цвет)



Индуктивный приёмник для скрытого ношения

Комплект подходит практически для любых аналоговых или цифровых раций. OnGuard III состоит из кнопки ответа РТТ-1, петличного микрофона и индуктивной петли скрытого ношения, которая надевается на шею.

OnGuard III может использоваться с гарнитурами RS7 или RS8. Обычно OnGuard III поставляется телесного цвета, по запросу доступен черный цвет. Комплект наиболее подходит для скрытого использования при секретных операциях.

Technical data:

Microphone:

Pattern:	electret
Directional:	omni-directional
Impedance:	2000 Ohm
Sensitivity:	-39 dB V / Pa, 1 kHz
Frequency:	300 Hz – 5 kHz

Speaker (Induct RS7):

Operating voltage:	1,4 V
Power input:	1 mA
Operating time:	approx. 80 hours
Battery type:	A 10
Weight (incl. battery):	1,5 g
Pattern:	magnetic
Sound pressure level:	max. 120 dB
Frequency range:	300 Hz – 5 kHz

Send button (PTT-1):

Housing:	Santoprene rubber, beige
Life cycle PTT:	min. 50.000 cycles

Additional data:

Temperature range:	-10°C to +40°C
Weight:	72 g (incl. PTT button)

Digital Standard approved

