

## AirTalk WL-DECT



Part-No.: 0250000-4



AirTalk XS-WL with QD plug (0110011-22) / VCS connector

The AirTalk WL-DECT is a wireless communication solution on DECT-Standard. It consists of 3 components which are independently available. The core item is the base station CA12 including a wireless send button from Plantronics (Part-No.: 0250000-4). Powered by a high-performing rechargeable battery it enables a speech time of up to 8 hours.

The second component of the AirTalk WL-DECT is the headset. You can use any headset of the WL-Series. Above, you can see the monaural version AirTalk XS-WL (Part-No.: 0110011-22). Thanks to a QD (Quick Disconnect) connector, it is possible to link different headsets to one base station. This is of advantage for Air traffic Controllers in shift operation.

Due to different VCS connectors available (3<sup>rd</sup> component), the WL-DECT is to use with any current Voice-Communication-System (VCS). For exact configuration of the AirTalk WL-DECT, please take a closer look at the pricelist.

### Technical data:

#### **Microphone (Headset):**

Pattern:	electret
Directional:	omni-directional
Impedance:	2200 Ohm
Sensitivity:	-40 dB V / Pa, 1 kHz
Frequency:	100 Hz – 10 kHz

#### **Speaker (Headset):**

Pattern:	dynamic
Impedance:	600 Ohm at 1mW / 1 kHz
Sound pressure level:	max. 91 dB
Frequency:	200 Hz – 10 kHz

#### **Additional data:**

Temperature range:	+4°C to +49°C
Response time PTT:	128 ms
Life cycle PTT:	3.000.000 cycles
Dimensions (LxWxH):	185 mm x 170 mm x 55 mm
Weight:	approx. 210 g (Mobile part)

TECHNICAL DATA